



CST70N10T N-Ch 100V Fast Switching MOSFETs



CST70N10T Features

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$


CST70N10T Product Summary

BVDSS	RDSON	ID
100V	8.5mΩ	70A

CST70N10T Applications

- DC-DC Converters
- Power management functions
- Synchronous-rectification applications

CST70N10T TO-220 Pin Configuration



CST70N10T Absolute Maximum Ratings:

Symbol	Parameter	Value	Units
V_{DSS}	Drain-to-Source Voltage	100	V
I_D	Continuous Drain Current	70	A
	Continuous Drain Current	45	A
I_{DM}^{a1}	Pulsed Drain Current	280	A
E_{AS}^{a2}	Single pulse avalanche energy	110	mJ
V_{GS}	Gate-to-Source Voltage	±20	V
P_D	Power Dissipation	100	W
T_J, T_{STG}	Operating Junction and Storage Temperature Range	150, -55 to 150	°C
T_L	Maximum Temperature for Soldering	260	°C

CST70N10T Thermal Characteristics:

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.25	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	64	°C/W



CST70N10T N-Ch 100V Fast Switching MOSFETs

CST70N10T Electrical Characteristics (TA= 25°C unless otherwise specified):

Static Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
V _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	100	--	--	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} =100V, V _{GS} =0V	--	--	1	μA
I _{GSS(F)}	Gate to Source Forward Leakage	V _{GS} =+20V, V _{DS} =0V	--	--	100	nA
I _{GSS(R)}	Gate to Source Reverse Leakage	V _{GS} =-20V, V _{DS} =0V	--	--	-100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.3	1.8	2.3	V
R _{DS(ON)}	Drain-to-Source On-Resistance	V _{GS} =10V, I _D =20A	--	8.5	10.5	mΩ
		V _{GS} =4.5V, I _D =15A	--	9.5	15	mΩ

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
C _{iss}	Input Capacitance	V _{GS} = 0V V _{DS} = 50V f = 1.0MHz	--	1368	--	pF
C _{oss}	Output Capacitance		--	451	--	
C _{rss}	Reverse Transfer Capacitance		--	12.9	--	
R _g	Gate resistance	V _{GS} =0V, V _{DS} Open	--	0.48	--	Ω

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
t _{d(ON)}	Turn-on Delay Time	I _D = 10A V _{DS} = 50V V _{GS} = 10V R _G = 4Ω	--	16	--	ns
t _r	Rise Time		--	10	--	
t _{d(OFF)}	Turn-Off Delay Time		--	40	--	
t _f	Fall Time		--	6	--	
Q _g	Total Gate Charge	V _{GS} = 10V	--	31.3	--	nC
Q _{gs}	Gate Source Charge	V _{DS} = 50V	--	3.49	--	
Q _{gd}	Gate Drain Charge	I _D = 10A	--	7.63	--	

Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Value			Value
			Min.	Typ.	Max.	
I _S	Diode Forward Current	T _C = 25 °C	--	--	70	A
V _{SD}	Diode Forward Voltage	I _S =10A, V _{GS} =0V	--	--	1.2	V
t _{rr}	Reverse Recovery time	I _S =10A, V _{DD} =50V dI/dt=100A/μs	--	103	--	ns
Q _{rr}	Reverse Recovery Charge		--	187	--	nC

a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: VDD=50V, L=0.3mH, Rg=25Ω, Starting T_J=25 °C




CST70N10T N-Ch 100V Fast Switching MOSFETs

CST70N10T Characteristics Curve:


Typ. output characteristics

$$I_D = f(V_{DS})$$




Typ. drain-source on resistance

$$R_{DS(on)} = f(I_D)$$




Typ. transfer characteristics

$$I_D = f(V_{GS})$$



Drain-source on-state resistance

$$R_{DS(on)} = f(T_j); I_D = 20A; V_{GS} = 10V$$






CST70N10T N-Ch 100V Fast Switching MOSFETs


Gate Threshold Voltage

$$V_{TH}=f(T_j); I_D=250\mu A$$




Drain-source breakdown voltage

$$V_{BR(DSS)}=f(T_j); I_D=250\mu A$$




Typ. gate charge

$$V_{GS}=f(Q_g); I_D=10A$$



Typ. capacitances


$$C=f(V_{DS}); V_{GS}=0V; f=1MHz$$






CST70N10T N-Ch 100V Fast Switching MOSFETs


Power Dissipation
 $P_{tot}=f(T_c)$




Maximum Drain Current
 $I_D=f(T_c)$



Safe operating area
 $I_D=f(V_{DS})$



Body Diode Forward Voltage Variation
 $I_F=f(V_{GS})$






CST70N10T N-Ch 100V Fast Switching MOSFETs

Max. transient thermal impedance


$$Z_{thJC} = f(t_p)$$






CST70N10T N-Ch 100V Fast Switching MOSFETs


CST70N10T Test Circuit and Waveform:



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms



CST70N10T N-Ch 100V Fast Switching MOSFETs

CST70N10T Mechanical Dimensions for TO-220

COMMON DIMENSIONS



SYMBOL	MM	
	MIN	MAX
A	9.70	10.30
B	3.40	3.80
C	8.80	9.40
D	1.17	1.47
E	2.60	3.50
F	15.10	16.70
G	19.55MAX	
H	2.54REF	
I	0.70	0.95
J	9.35	11.00
K	4.30	4.77
L	1.20	1.45
M	0.40	0.65
N	2.20	2.60