



PE5080G N-Channel Enhancement Mode Power MOSFET

PE5080G Description


The PE5080G uses deep trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. It can be used in a wide variety of applications.

PE5080G General Features


- $V_{DS} = 100V$, $I_D = 80A$
- $R_{DS(ON)} < 8m\Omega$ @ $V_{GS} = 10V$
- $R_{DS(ON)} < 10m\Omega$ @ $V_{GS} = 4.5V$
- High Power and current handing capability
- Lead free product is acquired

PE5080G Application


- PWM applications
- Load switch
- Power management



Schematic diagram



Marking and pin assignment



DFN5x6-8L

PE5080G Absolute Maximum Ratings (TC=25°C unless otherwise noted)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	80	A
Drain Current-Continuous ($T_C = 100^\circ C$)	$I_D(T_C = 100^\circ C)$	50	A
Pulsed Drain Current (Note 1)	I_{DM}	320	A
Maximum Power Dissipation	P_D	76	W
Single Pulse Avalanche Energy ($L = 0.5mH$)	E_{AS}	108	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	$^\circ C$

PE5080G Thermal Characteristic

Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.65	$^\circ C/W$
--------------------------------------	-----------------	------	--------------



PE5080G Electrical Characteristics (TC=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	100	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V, V_{GS}=0V$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.2	1.6	2.3	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=20A$	-	6.3	8	m Ω
		$V_{GS}=4.5V, I_D=15A$	-	8.5	10	m Ω
Forward Transconductance	g_{FS}	$V_{DS}=10V, I_D=20A$	-	70	-	S
Dynamic Characteristics (Note 4)						
Input Capacitance	C_{iss}	$V_{DS}=50V, V_{GS}=0V,$ $F=1.0MHz$	-	2710	-	pF
Output Capacitance	C_{oss}		-	810	-	pF
Reverse Transfer Capacitance (Note 4)	C_{rss}		-	41	-	pF
Gate Resistance	R_g	$F=1.0MHz$	-	1.9	-	Ω
Switching Characteristics						
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=50V, I_D=20A,$ $V_{GS}=10V, R_G=3\Omega$	-	20.2	-	nS
Turn-on Rise Time	t_r		-	11.7	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	61.7	-	nS
Turn-Off Fall Time	t_f		-	15.4	-	nS
Total Gate Charge	Q_g	$V_{DS}=50V, I_D=20A,$ $V_{GS}=10V$	-	49.2	-	nC
Gate-Source Charge	Q_{gs}		-	7	-	nC
Gate-Drain Charge	Q_{gd}		-	12.3	-	nC
Drain-Source Diode Characteristics						
Maximum Body-Diode Continuous Current	I_S				80	A
Diode Forward Voltage (Note 3)	V_{SD}	$V_{GS}=0V, I_S=10A$	-	0.85	1.2	V
Body Diode Reverse Recovery Time	t_{rr}	$I_F=50A, dI/dt=100A/\mu s$		65		ns
Body Diode Reverse Recovery Charge	Q_{rr}			133		nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to product.



PE5080G Typical Electrical and Thermal Characteristics




Figure 1 Switching Test Circuit




Figure 2 Switching Waveform




Figure 3 Power De-rating




Figure 4 Drain Current




Figure 5 Output Characteristics




Figure 6 Rdson vs Drain Current




Figure 7 Transfer Characteristics




Figure 9 $R_{DS(on)}$ vs V_{GS}




Figure 11 Gate Charge




Figure 8 $R_{DS(on)}$ vs Junction Temperature




Figure 10 Capacitance vs V_{DS}




Figure 12 Source- Drain Diode Forward




Figure 13 Safe Operation Area





Figure 14 Normalized Maximum Transient Thermal Impedance



PE5080G DFN5x6-8L Package Information



Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	0.800	1.050	1.200
b	0.250	0.350	0.490
c	0.254TYP.		
D	4.800	5.000	5.100
e	1.270TYP.		
E	5.650	5.800	5.900
E1	3.400TYP.		
F	1.300TYP.		
G	0.600TYP.		
H	5.950	6.080	6.200
J	0.950TYP.		
K	4.000TYP.		
L	-	-	0.150
L1	0.100	0.140	0.180
P	1.180TYP.		
θ	6°	10°	14°